

Tenant Circuit Breakers

UL Listed Short Circuit Current Rating depends on lowest interrupting rating of circuit breaker installed. (Refer to the table on the bottom of page 2-9 for Square D certified ratings for downstream panelboards and load centers.)

Table 2.10: Tenant Circuit Breakers


Amperes	10 k AIR 120/240 Vac	\$ Price (DE2A)	22 k AIR 120/240 Vac	\$ Price (DE2A)	42 k AIR 120/240 Vac	\$ Price (DE2A)	100 k AIR 120/240 Vac	\$ Price (DE2A)
For use in 125 A Max. Type MP, MPR and MPH Meter-Pak Metering Equipment								
40	QO240	67.00	QO240VH▲	146.00	QOH240	317.00	—	—
50	QO250	67.00	QO250VH▲	146.00	QOH250▲	317.00	—	—
60	QO260	67.00	QO260VH	146.00	QOH260▲	317.00	—	—
70	QO270	134.00	QO270VH	224.00	QOH270▲	528.00	—	—
80	QO280	189.00	QO280VH	315.00	QOH280▲	651.00	—	—
90	QO290	189.00	QO290VH	315.00	QOH290	651.00	—	—
100	QO2100	189.00	QO2100VH	315.00	QOH2100	651.00	—	—
125	QO2125	428.00	QO2125VH	1034.00	QOH2125	1389.00	—	—
For use in 200 A Max. Type MP, MPR and MPH Meter-Pak Metering Equipment								
100	QOM2100MM	474.00	QOM2100MVH	1143.00	—	—	—	—
125	QOM2125MM	474.00	QOM2125MVH	1143.00	—	—	—	—
150	QOM2150MM	474.00	QOM2150MVH	1143.00	—	—	—	—
175	QOM2175MM	474.00	QOM2175MVH	1143.00	—	—	—	—
200	QOM2200MM	474.00	QOM2200MVH	1143.00	—	—	—	—
Amperes	10 k AIR 120/240 Vac	\$ Price (DE2A)	25 k AIR 120/240 Vac	\$ Price (DE2A)	65 k AIR 120/240 Vac	\$ Price (DE2A)	100 k AIR 120/240 Vac	\$ Price (DE2A)
For use in 225 A MPL Lever Bypass Meter-Pak Metering Equipment								
40	QO240■	67.00	QO240VH▲◆■	146.00	QOH240■★	317.00	—	—
50	QO250■	67.00	QO250VH▲◆■	146.00	QOH250■★★▲	317.00	—	—
60	QO260■	67.00	QO260VH▲◆■	146.00	QOH260■★★▲	317.00	—	—
70	QBP22070TM	474.00	QDP22070TM	1143.00	QGP22070TM	1521.00	QJP22070TM	1890.00
80	QBP22080TM	474.00	QDP22080TM	1143.00	QGP22080TM	1521.00	QJP22080TM	1890.00
90	QBP22090TM	474.00	QDP22090TM	1143.00	QGP22090TM	1521.00	QJP22090TM	1890.00
100	QBP22100TM	474.00	QDP22100TM	1143.00	QGP22100TM	1521.00	QJP22100TM	1890.00
110	QBP22110TM	474.00	QDP22110TM	1143.00	QGP22110TM	1521.00	QJP22110TM	1890.00
125	QBP22125TM	474.00	QDP22125TM	1143.00	QGP22125TM	1521.00	QJP22125TM	1890.00
150	QBP22150TM	474.00	QDP22150TM	1143.00	QGP22150TM	1521.00	QJP22150TM	1890.00
175	QBP22175TM	474.00	QDP22175TM	1143.00	QGP22175TM	1521.00	QJP22175TM	1890.00
200	QBP22200TM	474.00	QDP22200TM	1143.00	QGP22200TM	1521.00	QJP22200TM	1890.00
225	QBP22225TM	474.00	QDP22225TM	1143.00	QGP22225TM	1521.00	QJP22225TM	1890.00

- ▲ Order only. Not stocked in PDS. Order Point: Lincoln.
- Requires use of EZM125QOA adapter (order separately). Refer to page 2-15 for pricing.
- ◆ QO-VH tenant circuit breakers are rated 22 kAIR at 120/240 Vac.
- ★ QOH tenant circuit breakers are rated 42 k AIR at 120/240 Vac.

QO2100VH
2P, Plug-on Type
Circuit Breaker



QDP22200TM
2P, Bolt-on Type
Circuit Breaker



QOM2200MVH

Accessories

Table 2.11: Accessories

Accessory	Description	Cat. No.	\$ Price
Fifth Jaw Kit	Fifth Jaw Kit	5J	18.30
Horn Bypass Kit	For MPR and MPH only	MMHB	16.70
QO Adapter	For Bolt-on Q2M tenant circuit breakers (40–125 A, 2P)	EZM125QOA	273.00
Slider Type Manual Circuit Closing:	125 A Ring Style 2 Position Top Meter (Only)	MM125MB▼	171.00
	125 and 200 A Ring Style	MM200MB▼	171.00
Sealing Rings:	Snap-on Aluminum	2920910001	8.00
	Screw Type Aluminum	29008W	20.10
	Snap-on Type Stainless Steel	ARP00026	16.70
Meter Cover-Lexan™	Meter Cover-Lexan™	29007	10.10
Optional Lug Kits:	(1) 1/0–600 AWG/kcmil or (2) 1/0–250 AWG/kcmil per phase	MMLK250△□	150.00
	(2) 3/0–500 AWG/kcmil per phase	MMLK500□	200.00
	(2) 2–600 AWG/kcmil per phase	MMLK600□	233.00
Semiflush Kits:	125 A 2 Position	MPSF12	101.00
	125 A 3–4 Position	MPSF14	134.00
	125 A 5–6 Position	MPSF16	218.00
	200 A 2–3 Position	MPSF23	144.00
	200 A 4 Position 200 A 5–6 Position	MPSF24 MPSF26	171.00 255.00
NEMA/EUSERC Lug Landing Kit:	For 3 through 6 position 125 A and 200 A devices. Each pad rated 600 A maximum and includes (2) 1/2-13 studs and mounting hardware.	MMSK2□	185.00
NEMA Lug Landing Kit:	For use ONLY on MPL43225, MPL53225 and MPL64225 with optional lugs. See wiring diagram of each device for optional lugs.	MMSK4	276.00
MP Meter-Pak Wireway: (Wall Mount Pedestal)	125 A 2 Position ONLY	MP43X8PED	441.00
	125 A 3–6 Position	MP43X11PED	504.00
	200 A 2–6 Position	MP43X11PED	504.00
	MPL32-225	MP35X11PED◇	504.00
	MPL53-225	MP43X11PED	504.00
MP Meter-Pak Wireway Extensions:	MPL64-225	MP35X11PED◇	504.00
	Used ONLY with MP43X8PED	MP12X8PEDEXT◇	102.00
	Used with MP43X11PED and MP35X11PED	MP12X11PEDEXT◇	126.00

- ▼ The meter center short circuit current rating is 10 kA when manual circuit closing is used. Not rated for continuous duty.
- △ Standard lug for 3 through 6 position 125 A and 2 through 4 position 200 A devices.
- Cannot be installed on 2 position 125 A device.
- ◇ Order only. Not stocked in PDS. Order point: Lexington.

For hubs and closing plates Page 2-3